

CLAIMS

What is claimed is:

1. An optical connector adapter comprising:

a housing having at least one passage formed therein for receiving a pair of connectors adapted to be mated to each other; and

a pair of latch inserts located in the at least one passage, each latch insert being adapted for locking a corresponding connector of the pair of connectors to the housing, and at least one latch insert of the pair of latch inserts having a spring loaded projection;

wherein the housing has at least one detent formed therein, the spring loaded projection on the at least one latch insert being biased into the at least one detent locking the at least one latch insert to the housing.

2. The optical connector adapter according to Claim 1, wherein the housing is a one-piece member.

3. The optical connector adapter according to Claim 1, wherein the housing has another detent and a second latch insert from the pair of latch inserts has another spring loaded projection which is biased into the other detent in the housing.

4. The optical connector adapter according to Claim 1, wherein the at least one detent is a recess formed in a side of the at least one passage.

AL

Sub A2

an outer housing with at least one passage
extending through the outer housing for mating
a pair of opposing connectors therein; and

wherein the outer housing is a one-piece member, the pair of inner housings being inserted into the at least one passage from opposite ends of the at least one passage.

14. The optical connector adapter according to Claim 13, wherein the interlocked complementing guide and guide rail align the at least one inner housing with another of the pair of inner housings in the at least one passage.

15. The optical connector adapter according to Claim 12, wherein the guide rail comprises a channel formed into a

side wall of the at least one passage, the channel being aligned with an insertion axis of the at least one passage.

16. The optical connector adapter according to Claim 13, wherein the at least one guide rail comprises a pair of guide rails, the guide rails being offset relative to each other at least in part so that a first one of the pair of guide rails allows insertion of one inner housing from one end of the passage, and a second one of the pair of guide rails allows insertion of a second inner housing from the opposite end of the passage.

17. The optical connector adapter according to Claim 12, wherein each inner housing of the pair of inner housings has a spring loaded latch, and the outer housing has detents formed therein, and wherein the spring loaded latch on each inner housing automatically engages the detents when each inner housing is inserted into the outer housing and locks each inner housing in the outer housing.

18. An optical connector adapter comprising:

an outer housing with at least one passage extending through the outer housing for mating a pair of opposing connectors therein; and

a pair of inner connector receptacles located in the passage, each inner connector receptacle being adapted for receiving a corresponding connector of the pair of opposing connectors and for locking the corresponding connector to the outer housing;

20250909 090614 6694

Sub
AZ

19. The optical connector adapter according to Claim 18, wherein the outer housing is a one piece member.

20. The optical connector adapter according to Claim 18, wherein the pair of guide rails are disposed on opposite sides of the at least one passage.

21. The optical connector adapter according to Claim 18, wherein the pair of guide rails are formed into walls of the at least one passage.

22. The optical connector adapter according to Claim 18, wherein the at least one passage comprises multiple passages each being adapted for mating a corresponding pair of opposing connectors therein.

23. The optical connector adapter according to Claim 18, wherein the outer housing is a one-piece member and has a mounting section which is angled at an acute angle relative to a centerline axis of the at least one passage.

24. A method for fabricating an optical connector adapter, the method comprising the steps of:

providing an outer housing which is a one piece member, the outer housing being adapted for mating a pair of optical connectors therein, and having at least one passage extending through the outer housing;

inserting a first inner housing into the at least one passage, the first inner housing having a first receptacle adapted for receiving a first connector of the pair of connectors;

securing the first inner housing to the outer housing;

inserting a second inner housing into the at least one passage, the second inner housing having a second receptacle adapted for receiving a second connector of the pair of connectors; and

securing the second inner housing to the outer housing;

wherein the first and second inner housings are inserted into the at least one passage through opposite ends of the at least one passage.

25. The method according to Claim 24, wherein securing the first inner housing comprises providing the first inner housing with a pair of spring loaded projections which engage detents in the outer housing when the first inner housing is inserted into the outer housing and lock the first inner housing in the outer housing.

26. The method according to Claim 24, wherein securing the second inner housing comprises providing the second

Sub
A2

~~g with a
detents i
g is inser
anner housi~~

add #3

[illegible]